

## GENERAL INFORMATION

LED Driver Type	Constant Voltage (Class 2)
Maximum Wattage	60 Watts
Input Voltage	120 VAC ± 10% Dedicated 120-277 VAC ± 10% Universal
Input Frequency	50/60Hz
Total Harmonic Distortion	<20%

## CASE STYLE I: METAL



## ELECTRICAL SPECIFICATIONS

Watts	Output Voltage	Max Output Current	Input Voltage	Input Power	Input Current	Power Factor	Efficiency	Hatch Part Number
60W	12 VDC	5.00A	120 - 277 VAC	71W	0.65/0.28A	>0.90	85%	LV60-12N-UNV-I
	12 VDC	5.00A	120 VAC	73W	0.64A	>0.90	82%	LV60-12N-120-I
	14 VDC	4.30A	120 - 277 VAC	71W	0.65/0.28A	>0.90	85%	LV60-14N-UNV-I
	24 VDC	2.50A	120 - 277 VAC	70W	0.65/0.28A	>0.90	86%	LV60-24N-UNV-I
	24 VDC	2.50A	120 VAC	69W	0.64A	>0.90	87%	LV60-24N-120-I

## PRODUCT FEATURES

- Short circuit and overload protection
- Over temperature protection
- Suitable for dry and damp locations
- Withstanding voltage: I/P – O/P 2kVAC
- Minimum start temp: -30°C

## APPROVALS

- UL 8750 recognized component
- EN61000-3-2
- EMC: Meets FCC47 CFR Part 15 (Class B) consumer limits
- UL879 SAM approved



## WARRANTY

- 5 year limited warranty

## RELATED PRODUCT

- Case Style F: 5.0" x 3.0" x 1.4"
- Case Style K: 9.6" x 1.9" x 1.5"
- Case Style R: 9.6" x 1.9" x 1.5"

## MECHANICAL SPECIFICATIONS: CASE STYLE I

### WIRING INFORMATION

Input:	12", Black (L), White (N) #18AWG
Output:	12", Red (+), Blue (-) #18AWG

### PACKAGING INFORMATION

Weight:	21.2 oz
Quantity:	20pc/carton

